

Form PTO-1390
(REV 10-95)

U.S. Department of Commerce Patent and Trademark Office

ATTORNEY'S DOCKET NUMBER

FMW-JJ-PCT-US

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/889500

INTERNATIONAL APPLICATION NO.
PCT/EP00/00421INTERNATIONAL FILING DATE
20 January 2000PRIORITY DATE CLAIMED
22 January 1999TITLE OF INVENTION: **DISK MOTOR WITH BEARING PRESTRESSING FEATURE**APPLICANT(S) FOR DO/EO/US: **EHRFELD, Wolfgang; STOLTING, Hans-Dieter; MICHEL, Frank;
NIENHAUS, Matthias, KLEEN, Stephan**

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Article 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2))
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3))
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

Form PTO-1390 (REV 10-95) page 2 of 2

PATENT COOPERATION TREATY
U.S. RECEIVING OFFICE
TO THE INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

Applicant: Wolfgang Ehrfeld
International Application No.: PCT/EP00/00421
International Filing Date: 20 January 2000
Title: DISK MOTOR WITH BEARING
PRESTRESSING FEATURE
Agent's Reference No.: FMW-JJ-PCT-US
Date: July 17, 2001

PRELIMINARY AMENDMENT

Sir:

Please amend the application as indicated below before calculation of the application fees as follows:

IN THE SPECIFICATION:

Please amend the application as indicated below.

Page 1:

Please replace the first paragraph as follows:

FIELD OF THE INVENTION

The invention relates to a disk motor with an armature disk (3), which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils.

09889500-10501

Page 1:

Please replace the second full paragraph as follows:

BACKGROUND OF THE INVENTION

Such disk motors are used as direct drives for turntables, for example. A basic explanation of disk motors can be found in H.-D. Stölting, A. Beisse, Elektrische Kleinmaschinen, Verlag Teubner, 1987, p. 169ff and p. 186ff.

Page 3:

Please replace the third full paragraph as follows:

SUMMARY OF THE INVENTION

The object of the current invention is to provide a disk motor that is characterized by a flat design, good smoothness of running and high torque.

Page 6:

Please replace fifth full paragraph as follows:

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 shows a vertical section through a disk motor.
- Figure 2 shows a vertical section through a disk motor as realized in another embodiment.
- Figure 3 shows an enlargement of the left portion of a sectional view of an embodiment modified from that shown in Figure 2 to illustrate the magnetic circuits.
- Figure 4 shows a top view of the coil arrangement shown schematically and
- Figures 5 - 13
- show the assembly of the disk motor shown in Figure 2.

Page 7:

Please replace the first full paragraph as follows:

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows a vertical section through a disk motor. The rotor comprises a shaft 1, which is inserted into an armature disk 3 and attached by its collar 2 to the armature disk 3. An annular permanent magnet 6 comprising permanent magnets with reversible polarity is located on the underside of the armature disk 3.

IN THE CLAIMS:

Please substitute the following claims for the pending claim of the same number.

1. (Amended) A disk motor comprising:
an armature disk, which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils, wherein
an annular soft-magnetic prestressing device is arranged concentrically on the stator plate in such a manner that at least one section of the prestressing device is located below the coil window of the coils in the axial direction.
2. (Amended) A disk motor as claimed in Claim 1, wherein the stator plate is of a non-magnetic material.

3. (Amended) A disk motor as claimed in Claim 1, wherein the annular prestressing device comprises a closed prestressing ring.
4. (Amended) A disk motor as claimed in Claim 1, wherein the annular prestressing device comprises at least one ring segment.
5. (Amended) A disk motor as claimed in Claim 1, wherein the armature disk supports an annular flux-return element opposite which the annular prestressing device is located in the radial direction.
6. (Amended) A disk motor as claimed in Claim 5, wherein the prestressing device has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element to the coil window.
7. (Amended) A disk motor as claimed in Claim 6, wherein the cross-section of the prestressing device becomes wider in the direction of the coil window.
8. (Amended) A disk motor as claimed in claim 6, wherein the prestressing device has a stepped cross-sectional contour.

IN THE ABSTRACT:

Please replace the original Abstract with the following Abstract:

ABSTRACT

The invention relates to a disk motor with an armature disk, which is rotatably mounted and provided with permanent magnets, and with a stator which comprises a stator plate which is equipped with coils. The aim of the invention is to provide a disk motor that is as flat as possible and that is characterized by an improved smoothness of running. To this end, an annular soft-magnetic prestressing device is arranged concentrically on the stator plate in such a manner that at least one section of the prestressing device is located below the coil window of the coils in the axial direction. The armature disk may support an annular flux-return element opposite which the annular prestressing device is located in the radial direction. Said prestressing device has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element to the coil window.

The following is a MARKED version of the amended pending claims, specification, and Abstract with all changes shown in conventional comparison.

Page 1:

Please replace the first paragraph as follows:

[Description] FIELD OF THE INVENTION

The invention relates to a disk motor with an armature disk (3), which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils.

Page 1:

Please replace the second full paragraph as follows:

BACKGROUND OF THE INVENTION

Such disk motors are used as direct drives for turntables, for example. A basic explanation of disk motors can be found in H.-D. Stölting, A. Beisse, Elektrische Kleinmaschinen, Verlag Teubner, 1987, p. 169ff and p. 186ff.

Page 3:

Please replace the third full paragraph as follows:

SUMMARY OF THE INVENTION

The object of the current invention is to provide a disk motor that is characterized by a flat design, good smoothness of running and high torque.

Page 6:

Please replace the forth full paragraph as follows:

[One embodiment of the current invention is described in greater detail below with reference to the attached drawings:]

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 shows a vertical section through a disk motor.
- Figure 2 shows a vertical section through a disk motor as realized in another embodiment.
- Figure 3 shows an enlargement of the left portion of a sectional view of an embodiment modified from that shown in Figure 2 to illustrate the magnetic circuits.
- Figure 4 shows a top view of the coil arrangement shown schematically and
- Figures 5 - 13 show the assembly of the disk motor shown in Figure 2.

Page 7:

Please replace the first full paragraph as follows:

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows a vertical section through a disk motor. The rotor comprises a shaft 1, which is inserted into an armature disk 3 and attached by its collar 2 to the armature disk 3. An annular permanent magnet 6 comprising permanent magnets with reversible polarity is located on the underside of the armature disk 3.

IN THE CLAIMS:

1. (Amended) A disk motor [with] comprising:
an armature disk, which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils, [characterized by the fact that] wherein
an annular soft-magnetic prestressing device [(20)] is arranged concentrically on the stator plate [(10)] in such a manner that at least one section of the prestressing device is located below the coil window [(18a, 18b)] of the coils [(17a, 17b)] in the axial direction.
2. (Amended) A disk motor as claimed in Claim 1, [characterized by the fact that] wherein the stator plate [(10)] is of a non-magnetic material.
3. (Amended) A disk motor as claimed in Claim 1 [or 2], [characterized by the fact that] wherein the annular prestressing device [(20)] comprises a closed prestressing ring [(21)].
4. (Amended) A disk motor as claimed in Claim 1 [or 2], [characterized by the fact that] wherein the annular prestressing device [(20)] comprises at least one ring segment.
5. (Amended) A disk motor as claimed in [one of the Claims] Claim 1 [through 4], [characterized by the fact that] wherein the armature disk [(3)] supports an annular flux-return element [(5)] opposite which the annular prestressing device [(20)] is located in the radial direction.

6. (Amended) A disk motor as claimed in Claim 5, [characterized by the fact that] wherein the prestressing device [(20)] has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element [(5)] to the coil window [(18a,b)].
7. (Amended) A disk motor as claimed in Claim 6, [characterized by the fact that] wherein the cross-section of the prestressing device [(20)] becomes wider in the direction of the coil window [(18a,b)].
8. (Amended) A disk motor as claimed in [one of the Claims] claim 6 [or 7], [characterized by the fact that] wherein the prestressing device [(20)] has a stepped cross-sectional contour.

IN THE ABSTRACT:

Please replace the original Abstract with the following Abstract:

ABSTRACT

The invention relates to a disk motor with an armature disk [(3)], which is rotatably mounted and provided with permanent magnets, and with a stator which comprises a stator plate [(10)] which is equipped with coils [(17a-f)]. The aim of the invention is to provide a disk motor that is as flat as possible and that is characterized by an improved smoothness of running. To this end, an annular soft-magnetic prestressing device [(20)] is arranged concentrically on the stator plate [(10)] in such a manner that at least one section of the prestressing device is located below the coil window [(18a, b)]

of the coils [(17a-b)] in the axial direction. The armature disk [(3)] may support an annular flux-return element [(5)] opposite which the annular prestressing device [(20)] is located in the radial direction. Said prestressing device [(20)] has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element [(5)] to the coil window.

Respectfully submitted,

HUDAK & SHUNK CO., L.P.A.



By: Daniel J. Hudak, Jr.
Registration No. 47,669

DJH/lb

7 West Bowery Street
Suite 808
Akron, OH 44308-1133
(330) 535-2220

Attorney Docket No.: FMW-JJ-PCT-US (I 788)

03/889500
JC18 Rec'd PCT/PTO 17 JUL 2001DISK MOTOR WITH BEARING PRESTRESSING FEATURE

Description:

The invention relates to a disk motor with an armature disk (3), which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils.

Such disk motors are used as direct drives for turntables, for example. A basic explanation of disk motors can be found in H.-D. Stölting, A. Beisse, Elektrische Kleinmaschinen, Verlag Teubner, 1987, p. 169ff and p. 186ff.

DE 34 25 805 A1 discloses a DC motor realized as a disk motor to rotate a mirror. The stator comprises a coil-insulating frame and a stator flange connected thereto, which flange completely encloses the rotor and protects it from external influences. The rotor has a shaft which is attached to the mirror and which has on its lower end a magnet holder equipped with a two-pole permanent magnet. The rotor shaft is mounted in two ball bearings secured in the stator flange. To minimize axial play, the outer rings of the ball bearing must be prestressed against the associated inner rings. To achieve this, the citation teaches that the stator flange fixes both outer rings, which are arranged one above the other, whereas the associated inner rings are stressed in the opposite direction by the dimensions of the rotor. The disadvantage of this arrangement, however, is that there are two ball bearings arranged one above the other and separated by some distance. A single bearing is desirable to reduce the overall height.

03889500-100501

To achieve high torques, disk motors are usually equipped with a soft-magnetic flux-return element, i.e. a closed magnetic circuit to increase the flux density in the air gap. The magnetic lines of electric flux are guided through ferromagnetic material with only small air gaps between the individual components. As explained in Stölting/Beisse, for example, this is realized by providing the circumference of the armature disk with an annular skirt, attached to which skirt is an annular flux-return element with which the flat coils of the stator are supported from underneath. The magnetic lines of electric flux run outward from the permanent magnets through the armature disk, down through the annular skirt and back to the permanent magnet through the annular flux-return element and the active region of the coil (cf. Stölting/Beisse, p. 186).

A disk motor of similar design is disclosed in German utility model DE-GM-75 419 11. The armature disk has at its center a bell-shaped spacer to which the annular flux-return element is fastened. The rotor housing is equipped with a bearing tube in which two porous bearings and an intermediary felt ring for the storage of oil are arranged for the radial bearing of the rotor shaft. For axial bearing, the housing has a floor plate with a tube-like extension, on the lower edge of which is attached a supporting member for a thrust bearing for the rotor shaft. The bottom end face of the rotor shaft is crowned and rests on the thrust bearing. The overall height of this motor is significantly greater than that of the motor disclosed in DE 34 25 805 A1 because it has a total of three bearings.

T.05007-0056860

Another variant of a disk motor with two ball bearings and a magnetic annular flux-return element is disclosed in DE 35 28 303 A1, which strives for a low overall height. The armature disk has a tube-like hub in which two ball bearings are arranged. The ball bearings are fixed at a defined distance to one another on a shaft stub attached to the stator plate. The function of the annular flux-return element is served by the stator plate, which must be manufactured of a suitable ferromagnetic material.

This disk motor has the following disadvantages: first there are two ball bearings with the associated additional assembly/installation costs; and second, the flux-return circuit does not run exclusively through the active region of the coils and thus does not contribute wholly to the generation of torque. Because the entire stator plate is involved in magnetic flux return, significant eddy currents are created which have a braking effect on the armature disk. Furthermore, attractive force is exerted on the armature disk in both the skirt region and the hub region, thus very large forces are exerted on the armature disk and in turn the bearings; significant bearing loads can result which under certain circumstances can lead to premature bearing failure. In addition, the entire bearing plate must be manufactured of ferromagnetic material and be of the same diameter as the armature disk. The motor is heavy as a result.

The object of the current invention is to provide a disk motor that is characterized by a flat design, good smoothness of running and high torque.

To achieve this object, the current invention teaches that an annular soft-magnetic prestressing device is arranged

concentrically on the stator plate in such a manner that at least one section of the prestressing device is located below the coil window of the coils in the axial direction.

The advantage of the current invention lies in the fact that the magnetic prestressing eliminates the axial play of the armature disk bearing, so that an appropriate smoothness of running can also be achieved using only a single bearing, e.g. a ball bearing or a plain bearing. If a single bearing is sufficient, overall height is significantly reduced, yet there is still enough space for the bearing that commercially available ball bearings can be used.

If the disk motor is realized as a micromotor, commercially available bearings are understood to be those having an overall height of 1 mm or more. The advantage of commercially available bearings is that overall manufacturing costs are lower than if two custom bearings with extremely low overall heights must be used. The magnetic prestressing as taught by the current invention thus permits optimization of running characteristics with a lower overall height.

It has been demonstrated that providing the stator plate with a closed ring, or at least a ring segment, of a soft-magnetic, in particular a ferromagnetic, material is sufficient for the magnetic prestressing. The magnitude of the magnetic prestressing can be set via the width of the prestressing ring or ring segment with no change in the overall height, thus enabling adaptation to the geometry of the armature disk and the bearing used. This avoids unnecessarily large bearing loads, and thus can significantly extend the service life of the motor.

It is preferred that the radial width of the prestressing device be \leq the corresponding width of the coil window.

By arranging at least one section of the prestressing device below the coil window of the coils in the axial direction, whereby the inner regions of the coil where the magnetic lines of electric flux run parallel to the coil axis are understood, the magnetic prestressing circuit also contributes to the generation of torque.

It is advantageous if the prestressing device includes a material with high ohmic resistance to prevent eddy currents.

Because the prestressing device is arranged on the stator plate, in particular on the top of the stator plate, there is no housing between the prestressing device and the coil window to adversely affect the magnetic field. The advantage of this is that the stator material can be freely chosen.

As taught by another embodiment, the armature disk can support an annular flux-return element which extends below the coils. In this case, the prestressing device is arranged as to be opposite the annular flux-return element in the radial direction. By locating the prestressing device below the coil window, the prestressing device becomes an element of the magnetic flux return and thus all of the magnetic lines of electric flux are used wholly for the generation of torque.

It is also advantageous that the prestressing device has a contour that guides the magnetic lines of electric flux from the annular flux-return element to the coil window.

The prestressing device preferably becomes wider in the direction of the coil window. A stepped cross-sectional contour, for example, is advantageous as it also permits a gearing with the stator plate.

A further advantage is that the material for the stator plate can be freely chosen because it does not have to be involved in magnetic flux return. Lightweight materials can therefore be used to reduce the weight of the motor.

The stator plate is preferably of a non-magnetic, preferably diamagnetic, material. This also applies to the armature disk bearing. This prevents the lines of electric flux from running over the bearing, which would adversely affect running smoothness. Here a non-magnetic material is understood as one that is neither a soft nor hard-magnetic material.

The stator plate must only be designed such that the prestressing ring can be securely held, for example. This also contributes to a compact design.

One embodiment of the current invention is described in greater detail below with reference to the attached drawings.

- Figure 1 shows a vertical section through a disk motor.
- Figure 2 shows a vertical section through a disk motor as realized in another embodiment.
- Figure 3 shows an enlargement of the left portion of a sectional view of an embodiment modified from that shown in Figure 2 to illustrate the magnetic circuits.
- Figure 4 shows a top view of the coil arrangement shown schematically and
- Figures 5 - 13 show the assembly of the disk motor shown in Figure 2.

Figure 1 shows a vertical section through a disk motor. The rotor comprises a shaft 1, which is inserted into an armature disk 3 and attached by its collar 2 to the armature disk 3. An annular permanent magnet 6 comprising permanent magnets with reversible polarity is located on the underside of the armature disk 3.

The stator comprises a stator plate 10 to which the outer ring 15 of a commercially available ball bearing 14 is fastened. The inner ring 16 of the ball bearing 14 rests against the shaft 1. Flat coils 17a and 17b are fastened to the top 12 of the stator plate 10, with the arrangement of the coils 17a and 17b such that the coil windows 18a,b formed by the interior space within the coil windings, are located below the annular permanent magnet 6. The flat coils 17a,b and the stator plate 10 can also be integrated into a monobody component.

A prestressing device 20 in the form of a prestressing ring 21 is inset into the stator plate 10. The arrangement of the prestressing ring 21 is chosen such that it extends below the coil windows 18a, 18b of the coils 17a, 17b in the axial direction by some amount \leq the size of the coil window. As a result, the prestressing ring 21 / magnetic lines of electric flux contribute to the generation of torque.

The overall height of the disk motor is low and primarily defined by the height of the ball bearing 14.

Figure 2 shows a disk motor with flux return. An annular skirt 4 extending downward and supporting an annular flux-return element 5 is fastened to the circumference of the armature disk 3. The stator plate 10 has a central bore 13 which seats the ball bearing 14, whereby the outer ring 15 is immovably held in the bore 13. Flat coils 17 a and d, which extend into the space

between the annular flux-return element 5 and the armature disk 3, are fastened to the top 12 of the stator plate 10. The coil arrangement shown in Figure 2 with flat coils 17a and d and the associated coil windows 18a and d corresponds to a section along the line II-II through the coil arrangement shown schematically in Figure 4. The stator plate 10 has at its outer edge an annular step 11 in which the prestressing ring of ferromagnetic material is fastened. The arrangement of the prestressing ring 21 is chosen such that it is opposite the annular flux-return element 5 in the radial direction. Because the stator plate 10 is not involved in magnetic flux return, the diameter of the stator plate 10 is only as large as the outside diameter of the prestressing ring. The material for the stator plate 10 can be chosen freely.

Figure 3 shows an enlargement of a vertical section through an embodiment of a disk motor that has been modified from that shown in Figure 2. The magnetic flux return is shown schematically as the closed circuit 23 ("main circuit") indicated by the arrows and the prestressing circuit 22 indicated by the broken line. The main circuit 23 runs through the armature disk 3, the annular skirt 4, the annular flux-return element 5 and the coil window 18a of the coil 17a.

Because of the arrangement of the prestressing ring 21 as taught by the current invention, the magnetic lines of electric flux of the prestressing circuit 22 also run through the coil window 18a, so that this magnetic prestressing circuit 22 contributes to the generation of torque. Furthermore, because the prestressing circuit 22 is arranged as taught by the current invention as part of the magnetic flux return, the magnetic prestress can be set independent of the magnetic flux return and independent of the total torque of the disk motor by varying the width of the prestressing ring 21 in the coil window 18a. The cross-sectional contour of the prestressing ring 21 is designed to redirect the

magnetic lines of electric flux to the coil window 18a, and therefore has a step 24. As a result, the prestressing ring 21 becomes wider in the direction of the coil window 18a, while at the same time forming a gearing for a better hold on the stator plate 10.

The magnetic prestressing causes the armature disk 3 to be attracted toward the stator plate 10, pulling the inner ring 16 of the ball bearing 14 downward. Because the outer ring 15 is immovably held in the stator plate 10, any axial play of the ball bearing 14 is eliminated.

Embodiment

The embodiment relates to a design as shown schematically in Figures 2 and 3. The disk motor has an outside diameter of 12.8 mm and is 1.4 mm high.

The motor has a torque constant of $0.40 \mu\text{Nm/Ma}$. The motor can easily be used for rotational speeds of up to 20,000 rpm while exhibiting good running characteristics.

Due to the design, the ball bearing is not influenced by the magnetic field. An attractive force in the Mn range is exerted by the magnetic prestressing.

The annular permanent magnet is manufactured by means of micro injection molding or sizing of an NdFeB powder containing a plastic as binder.

The annular magnet is approximately $300 \mu\text{m}$ thick.

The annular magnet is axially magnetized such that it has eight poles (four pole pairs) on the end face.

Miniaturized flat coils are manufactured by means of UV-deep lithography and subsequent galvanic precipitation.

The flat coils comprise two superimposed printed conductors separated by a polyimide film as a carrier. There are six coils, with the opposing coil pairs connected in series.

The flat coils are approximately $250\text{ }\mu\text{m}$ high.

Alternatively, the coils can be manufactured as multi-layer printed circuit boards (PCB) using micro precision laser technology.

The air gap between the coils and the rotating motor components is only approximately $80^{\circ}\mu\text{m}$.

Control is by means of a three-phase rectangular pulse signal, which in another embodiment is generated by a digital control unit integrated into a board bearing the disk motor.

FeSi is used as the soft-magnetic material for individual components such as the armature disk and annular flux-return element. Inexpensive mass production, such as by means of stamping and deep drawing, is made possible by the design of the components. The individual components are assembled together on an assembly platform, whereby only linear movements are made in only one assembly direction.

Figure 4 shows the design of the flat coils 17a-f. The coils 17a-f comprise superimposed films 26 with printed conductors, whereby the printed conductors of the individual films are connected to one another by the contact points 19, of which only two are identified. Radially opposed coils are connected in series to achieve a three-phase motor configuration.

Figures 5 - 13 show one assembly option for the disk motor shown in Figure 2, whereby the "a" figure shows the condition before and the "b" figure shows the condition after installing an additional component.

Assembly requires a mounting plate into which the individual components are inserted. Figure 5a shows the annular flux-return element 5 being inserted into the mounting plate 25. This is followed by the stator plate 10 (Figures 6a and b) and the setting of the prestressing ring 21 in the stator plate 10 (Figures 7a,b). In the next step (Figures 8a and b), the coils 17a-f are installed. The coils 17a-f are then mechanically and electrically connected to the contact pins 29a,b in the stator plate 10, which pins 29a,b lead to the outside.

The ball bearing 14 is then friction set (Figures 9a and 9b). In a further step, the shaft 1 is installed (Figures 10a and 10b) and the armature disk 3 with the annular permanent magnet 6 is placed on the shaft (Figures 11a and b).

Figures 12a and 12b show the friction setting of the armature disk 3 using a force die 27. The last step is the riveting of the armature disk using a riveting die 28 (Figures 13a and 13b).

Reference Numbers:

1	Shaft
2	Collar
3	Armature disk
4	Annular skirt
5	Annular flux-return element
6	Annular permanent magnet
10	Stator plate
11	Annular step
12	Top
13	Central bore
14	Ball bearing
15	Outer ring
16	Inner ring
17a-f	Coil
18a-f	Coil window
19	Contact point
20	Prestressing device
21	Prestressing ring
22	Magnetic prestressing circuit
23	Magnetic main circuit
24	Step
25	Mounting plate
26	Film
27	Force die
28	Riveting die
29a,b	Contact pin

Claims:

1. Disk motor with an armature disk, which is rotatably mounted and provided with permanent magnets, and with a stator comprising a stator plate which is equipped with coils, characterized by the fact that

an annular soft-magnetic prestressing device (20) is arranged concentrically on the stator plate (10) in such a manner that at least one section of the prestressing device is located below the coil window (18a, 18b) of the coils (17a, 17b) in the axial direction.
2. Disk motor as claimed in Claim 1, characterized by the fact that the stator plate (10) is of a non-magnetic material.
3. Disk motor as claimed in Claim 1 or 2, characterized by the fact that the annular prestressing device (20) comprises a closed prestressing ring (21).
4. Disk motor as claimed in Claim 1 or 2, characterized by the fact that the annular prestressing device (20) comprises at least one ring segment.
5. Disk motor as claimed in one of the Claims 1 through 4, characterized by the fact that the armature disk (3) supports an annular flux-return element (5) opposite which the annular prestressing device (20) is located in the radial direction.

6. Disk motor as claimed in Claim 5, characterized by the fact that the prestressing device (20) has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element (5) to the coil window (18a,b).
7. Disk motor as claimed in Claim 6, characterized by the fact that the cross-section of the prestressing device (20) becomes wider in the direction of the coil window (18a,b).
8. Disk motor as claimed in one of the Claims 6 or 7, characterized by the fact that the prestressing device (20) has a stepped cross-sectional contour.

T05007 00553360

Abstract

The invention relates to a disk motor with an armature disk (3), which is rotatably mounted and provided with permanent magnets, and with a stator which comprises a stator plate (10) which is equipped with coils (17a-f). The aim of the invention is to provide a disk motor that is as flat as possible and that is characterized by an improved smoothness of running. To this end, an annular soft-magnetic prestressing device (20) is arranged concentrically on the stator plate (10) in such a manner that at least one section of the prestressing device is located below the coil window (18a, b) of the coils (17a-b) in the axial direction. The armature disk (3) may support an annular flux-return element (5) opposite which the annular prestressing device (20) is located in the radial direction. Said prestressing device (20) has a cross-sectional contour that guides the magnetic lines of electric flux from the annular flux-return element (5) to the coil window.

T0500T-00568860

PTO/SB/01 (4-96)

Approved for use through 9/30/98 OMB 0651-0032

Type a plus sign (+) inside this box →  Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION	Attorney Docket No.	FMW-JJ-PCT-US (I 788)
	First Named Inventor	EHRFELD, Wolfgang
	COMPLETE IF KNOWN	
	Application Number	
	Filing Date	
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"DISK MOTOR WITH BEARING PRESTRESSING FEATURE"

(Title of the invention)

the specification of which

☐ is attached hereto
OR

☒ was filed on (MM/DD/YYYY) **01/20/00** as United States Application Number or PCT International

Application Number **PCT/EP00/00421** and was amended on (MM/DD/YYYY) **00/00/0000** (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119 (a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
199 02 371.9	DE	01/22/1999		Yes	No
				<input type="checkbox"/>	<input checked="" type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

(July 1996)

096893500-100501

Type a plus sign (+) inside this box → ☐

DECLARATION

Page 2

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
	PCT/EP00/00421	01/20/2000	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority sheet attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Name	Registration Number	Name	Registration Number
HUDAK, Daniel J.	25,879	TYRPAK, Michele M.	42,192
SHUNK, Laura F.	31,423	HUDAK, Daniel J. Jr.	47,669
ROTE, Frank C. Jr.	20,395	FARINE, Cheryl L.	36,796
SHUST, Nestor, W.	23,034		

☐ Additional registered practitioner(s) named on a supplemental sheet attached hereto.

Direct all correspondence to:

Name	HUDAK & SHUNK CO., L.P.A.		
Address	7 West Bowery Street, Suite 808		
Address			
City	Akron	State	Ohio
Country	US	Telephone	330-535-2220
		Fax	330-535-1435
		ZIP	44308-1133

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name	Wolfgang	Middle Initial	
Family Name	EHRFELD	Suffix e.g. Jr.	
Inventor's Signature	Wolfgang Eherfeld		Date 02.07.01
Residence: City	Mainz	State	
		Country	Germany
		Citizenship	DE
Post Office Address	Kehlweg 22		
Post Office Address			
City	Mainz	State	
		ZIP	D-55122
		Country	Germany

☒ Additional inventors are being named on supplemental sheet(s) attached hereto.

Type a plus sign (+) inside this box → ☒

DECLARATION						ADDITIONAL INVENTOR(S) Supplemental Sheet	
Name of Additional Joint Inventor, if any: <u>J D</u>						<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name	<u>Hans-Dieter</u>		Middle Initial	Family Name		<u>STÖLTING</u>	
Inventor's Signature	<u>X Hans-Dieter Stöltig</u>					Date	<u>28.07.01</u>
Residence: City	<u>Garbsen</u>	State	<u>DE</u>	Country	<u>Germany</u>	Citizenship	<u>DE</u>
Post Office Address	<u>Grandkuhle 4</u>						
Post Office Address							
City	<u>Garbsen</u>	State		ZIP	<u>D-30823</u>	Country	<u>Germany</u>
Name of Additional Joint Inventor, if any: <u>S D</u>						<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name	<u>Frank</u>		Middle Initial	Family Name		<u>MICHEL</u>	
Inventor's Signature	<u>X Frank Michel</u>					Date	<u>10.07.01</u>
Residence: City	<u>Nieder-Olm</u>	State	<u>Mainz</u>	Country	<u>Germany</u>	Citizenship	<u>DE</u>
Post Office Address	<u>Ebersheimer Strasse 4</u>						
Post Office Address	<u>Trajanstrasse 16</u>						
City	<u>Nieder-Olm</u>	State		ZIP	<u>D-55268</u> <u>D-55131</u>	Country	<u>Germany</u>
Name of Additional Joint Inventor, if any: <u>J D</u>						<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name	<u>Matthias</u>		Middle Initial	Family Name		<u>NIENHAUS</u>	
Inventor's Signature	<u>X Matthias Nienhaus</u>					Date	<u>24.07.01</u>
Residence: City	<u>Mainz</u>	State		Country	<u>Germany</u>	Citizenship	<u>DE</u>
Post Office Address	<u>St. Sebastian-Strasse 6</u>						
Post Office Address	<u>Hinter den Wiesen 7</u>						
City	<u>Mainz</u>	State		ZIP	<u>D-55128</u> <u>D-55127</u>	Country	<u>Germany</u>
Name of Additional Joint Inventor, if any: <u>S D</u>						<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name	<u>Stephan</u>		Middle Initial	Family Name		<u>KLEEN</u>	
Inventor's Signature	<u>X Stephan Kleen</u>					Date	<u>12.07.01</u>
Residence: City	<u>Mainz</u>	State		Country	<u>Germany</u>	Citizenship	<u>DE</u>
Post Office Address	<u>Boppstrasse 64</u>						
Post Office Address	<u>Reichklarastrasse 2</u>						
City	<u>Mainz</u>	State		ZIP	<u>D-55118</u>	Country	<u>Germany</u>

☐ Additional inventors are being named on supplemental sheet(s) attached hereto.

(July 1996)

T05001-00563660